


# TECHNICAL DATA KÄHR'S LUXURY TILES



**Loose Lay Stone** 500 x 500 x 5.0 x 0.5 mm  
2.5 m<sup>2</sup>/box






**Loose Lay Wood** 228.6 x 1219 x 5.0 x 0.5 mm  
1.95 m<sup>2</sup>/box

## PRODUCT











Loose Lay LVT	EN ISO 10582	Luxury Vinyl Tile
Application	EN ISO 10874	23/32



## SPECIFICATION

Thickness		EN ISO 24337	5.0 mm
Weight		EN ISO 24342	9.7 kg/m <sup>2</sup>
Wear layer		EN ISO 24346	0.5 mm

## PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	 EN 13501-1	Bfl-s1
Residual indentation	 EN 433	< 0.1 mm
Dimensional stability	 EN 434	≤ 0.15 %
Colour fastness	 EN ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R10
Electrical propensity	 EN 1815	< 2 kV (antistatic)
Wear resistance	 EN 660-2	< 2.0 mm <sup>3</sup> (Class T)
Chemical resistance	 EN ISO 26987	Pass with good results
Effect of castor chair	 EN 425	Suitable
Underfloor heating		Ok (max +27 °C)
Bacterial growth		Does not act as substrate

Cleaning and maintenance instructions, see: [www.kahrs.com](http://www.kahrs.com)

