




TECHNICAL DATA


UPOFLOOR QUARTZ



Mosaic, Uni, Tema
12" x 12" (304.8 x 304.8 mm)



Uni, Lines
12" x 24" (304.8 x 609.6 mm)



Mosaic, Tema
24" x 24" (609.6 x 609.6 mm)

Standard Specification	ASTM F1066
Thickness	0.08" (2.0 mm)
Weight	0.82 lbs/ft ² (4000 g/m ²)
Size / Area per box	Mosaic, Uni, Tema 12" x 12" (304.8 x 304.8 mm) / 58 pcs / 58 ft ² (5.39 m ²) Mosaic, Tema 24" x 24" (609.6 x 609.6 mm) / 12 pcs / 48 ft ² (4.46 m ²) Uni, Lines 12" x 24" (304.8 x 609.6 mm) / 24 pcs / 48 ft ² (4.46 m ²)
ASM D2047 Static Coefficient of Frictions	≥ 0.5 SCOF
ANSI B101.3-2012 Wet Dynamic Coefficient Of Friction Common Hard Surface Flooring Materials	Acceptable
Static Load Limit ASTM F970	3500 PSI
Critical Radiant Flux ASTM E648	> 0.45 watts/sq.cm Meets or exceeds Class 1 rating in NFPA Life Safety Code 101 and IBC 804.2 classification
Smoke Generation ASTM E662	< 450 Flaming and Non-Flaming
Effect of Castor Chair EN 425	Suitable No delamination
Chemical Resistance ASTM F925	Good resistance to most acids, alkalis, and solvents
Bacterial growth	Surface does not act as a substrate for bacterial growth
VOC Emissions CA 01350	Low Emitting Material Floorscore Certificate #: SCS-FS-02258
Warranty	20 Years Residential 10 Year Commercial

