

# Kahrs Condensed Guide Spec

All other information is available at [kahrs.com](http://kahrs.com)

GUIDE SPECIFICATION

09 64 33.04

## STUDIO COLLECTION

### STUDIO AND MEGA STUDIO

Kahrs International, Inc.  
940 Centre Circle, Suite 1000  
Altamonte Springs, FL 32714  
Telephone: 407-260-90910  
Fax: 407-260-9933  
Toll Free: 800-800-5247  
E-mail  
<http://www.kahrs.com>

## SECTION 09 64 33.04

### ENGINEERED WOOD STRIP FLOORING

#### PART 1 - PRODUCTS

##### 1.1 ENGINEERED WOOD STRIP FLOORING

- A. Product[s]: Subject to compliance with requirements, provide Strip and Mega Strip Hardwood Flooring by Kahrs International Inc.
1. Two layered laminated wood flooring consisting of a sliced plain sawn wearing layer in choice of wood species, design and finish.
  2. Backing layer of sawn Spruce.
  3. Solid tongue and groove construction, 7/16-inch (11-mm) thickness for glue-down and staple down applications only.
  4. Length: Manufacturer's standard.
  5. Edges: As indicated by product designation above.
  6. Finish: Manufacturer's standard UV cured acrylic urethane or oiled finish in color selected by Architect from full range.
  7. Wood Species, Design, and Finish [WF-#]: **<insert product description from web site>**.

##### 1.2 UNDERLAYMENTS

- A. Kahrs QuietStride underlayment plus vapor retarder complying with ASTM D 4397, polyethylene sheet not less than 6.0 mils (0.15 mm) thick. Kahrs approved moisture sealer may be substituted for 6.0 mil polyethylene sheet for QuietStride installations.

### **1.3 ACCESSORY MATERIALS**

- A. Wood Flooring Adhesive: Mastic recommended by flooring and adhesive manufacturers for application indicated.
- B. Wood Trim: In same species and grade as wood flooring, unless otherwise indicated.
  - 1. Wood Base: Manufacturer's standard.
  - 2. Quarter Round Molding: Manufacturer's standard.
  - 3. T- Molding: Manufacturer's standard.
  - 4. Threshold: Tapered on each side and routed at bottom of one side to accommodate wood flooring.
  - 5. Reducer Strip: Manufacturer's standard.
  - 6. Square Nose Reducer Strip: Manufacturer's standard.
  - 7. Trim Fasteners: As recommended by manufacturer.
- C. Cleaning Agent: Kahrs Wood Floor Cleaner.